

ITEM	PART NAME	Q'TY	MATERIAL	FINISH
1	Insulator	1	THERMOPLASTIC	Black, UL94V-0
2	CONTACT	24	HIGH CONDUCTIVITY COPPER	Contact area:Gold plated over Ni .
3	SHELL	1	STAINLESS STEEL	Ni plated over all
4	MID-PLATE	1	STAINLESS STEEL	Ni plated over all
5	GND-PLATE	1	STAINLESS STEEL	Cleaning

NOTE:

- MECHANICAL:
  - 1-1.MATING FORCE: 0.5~2.0Kgf
  - 1-2.UMMATING FORCE: Initial: 0.8~2.0Kgf  
After 500 to 10,000cycles: 0.6~2.0Kgf
  - 1-3.FREQUENCE:200±50 CYCLES/HOUR,10000 CYCLES;
- ELECTRICAL CHARACTERISTICS:
  - 2-1. CURRENT RATING: 1.25A/PIN FOR FOR VBUS AND GND  
0.25 A FOR OTHER PINS
  - 2-2. INITIAL CONTACT RESISTANCE:40mΩ Max.
  - 2-3. INSULATION RESISTANCE:100MΩ MIN
  - 2-4. WITHSTANDING VOLTAGE:100V AC,1 MINUTE;
- ENVIRONMENTAL  
TEMPERATURE RANGE: -25°C TO +85°C.

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

TOLERANCE UNSPECIFIED

X. ±0.40 X'. ±5'  
 X.X ±0.30 X.X' ±4'  
 X.XX ±0.25 X.XX' ±3'  
 X.XXX±0.15 X.XXX' ±2'

DRAWN/ DATE	设计	HMY
CHECKED/ DATE	审核	LYX
APPROVED/ DATE	核准	LJP

**深圳市步步精科技有限公司**

TITLE:  
TYPE-C 24P 沉板1.1 L=8.0 CHO.47 带EMI 编带 不带LOGO (JAE)

SIZE:A4	UNIT:MM.	PART. NO:	UC.01.32-1G-0002
SCALE: 1:1	PROJECTION	REV.:	版本
DWG. PATH		SHEET:	页码




NOTES

- 1. NUMBER OF CONNECTORS: 1050PCS/REEL
- 2. LEAD TAPE LENGTH

EMPTY 15PCS	PART 1050PCS	EMPTY 15PCS
LEADER 240mm	COMPONENT SUPPLIER	TRAILER 240mm

- 3. QUANTITY: 10500/CARTON
- 4. WEIGHT :
  - 4.1 NET WEIGHT : 4.94 Kg
  - 4.2 GROSS WEIGHT : 9.2 Kg



Input material direction

Cover tape

Direction of Production

REELX10

PE BAG

Note: You should put two desiccants in each PE bag

Adhesive tape

Angle bead

CARTON



TOLERANCE UNSPECIFIED		深圳市步步精科技有限公司 TITLE: TYPE-C 24P 沉板1.1 L=8.0 CH0.47 带EMI 编带 不带LOGO (JAE)			
X. ±0.40	X'. ±5'	SIZE:A4	UNIT:MM.	PART. NO:	UC. 01. 32-1G-0002
X.X ±0.30	X.X' ±4'	CHECKED/ DATE	SCALE: 1:1	PROJECTION	REV.: 版本
X.XX ±0.25	X.XX' ±3'	APPROVED/ DATE	DWG. PATH	0382-1	SHEET: 页码
X.XXX±0.15	X.XXX'±2'				