




Poles	DIM.A	DIM.B
2	3.96	7.9
3	7.92	11.8
4	11.88	15.8
5	15.84	19.7
6	19.80	23.7
7	23.76	27.7
8	27.72	31.6
9	31.68	35.6
10	35.64	39.5
11	39.60	43.5
12	43.56	47.5
13	47.52	51.4
14	51.48	55.4
15	55.44	59.3

技术参数 SPECIFICATIONS

- 间距: 3.96 Pitch: 3.96
- 极数: 2-15 Poles: 2-15
- 额定电压: AC,DC, 250V(有效值)
Rated voltage: AC,DC, 250V(rms)
- 额定电流: 3.0A AC,DC
Rated Current: 3.0A AC,DC
- 耐压值: 1000V AC/minute
Withstand voltage: 1000V AC/min.
- 工作温度: -25° C ~ +85° C
Working Temp : -25° C ~ +85° C
- 绝缘电阻: ≥1000 MΩ
Insulation resistance: ≥1000 MΩ
- 接触电阻: ≤20mΩ
Contact resistance: ≤20mΩ

材料 MATERIAL

- 塑胶: 尼龙 (Nylon) , UL94-V0
- Pin: 黄铜 (Brass)


包装方式 PACKAGE

- 袋装 Bag Package




THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X*: ±3* .X*: ±2* .XX*: ±1*	
APPD.	JM_Zheng	NAME: VH-2A (3.96-2P) 直针 米色	
CHKD.	LYX	PJ. NO.: WT.03.61-11-1001	
DR.	SGF	SIZE: A4 DRW NO.:	
PDWG.NO: 0102-1		FINISH: SEE NOTES MAT'L.: SEE NOTES	
		SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2	

PE袋规格:***X*** (以实际出货为准)



成品标签



1. 包装要求:

- 1.1 每PE袋包装1000 pcs;
- 1.2 每1袋放一小纸盒;
- 1.3 每20个小纸盒放一个纸箱, 共计20000PCS
- 1.4 纸箱外贴上标签



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		 深圳市步步精科技有限公司	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X*: ±3" .X*: ±2" .XX*: ±1"	
APPD.	JM_Zheng	NAME: VH-2A (3.96-2P) 直针 米色	
CHKD.	LYX	PJ. NO.: WT.03.61-11-1001	
DR.	SGF	SIZE: A4 DRW NO.:	
PDWG.NO: 0102-1		FINISH: SEE NOTES MAT'L.: SEE NOTES	
		SCALE: N/A REV.: A0 UNIT: mm PAGE: 2/2	