








REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0				

1. 技术参数:  
 1.1 额定电流: 0.5A AC/DC  
 1.2 额定电压: 50V  
 1.3 耐电压: 500V ACminute  
 1.4 接触电阻: 20mΩ MAX  
 1.5 绝缘电阻: 100MΩ MIN  
 2. 工作温度: -25℃~+85℃



Since 1987

步步精科技



Circuits	Dimensions (mm)			Circuits	Dimensions (mm)		
	A	B	C		A	B	C
0.8WT-2P	0.8	3.90	1.90	0.8WT-12P	8.80	11.90	9.90
0.8WT-3P	1.6	4.70	2.70	0.8WT-13P	9.60	12.70	10.70
0.8WT-4P	2.4	5.50	3.50	0.8WT-14P	10.40	13.50	11.50
0.8WT-5P	3.2	6.30	4.30	0.8WT-15P	11.20	14.30	12.30
0.8WT-6P	4.0	7.10	5.10	0.8WT-16P	12.00	15.10	13.10
0.8WT-7P	4.8	7.90	5.90				
0.8WT-8P	5.6	8.70	6.70				
0.8WT-9P	6.4	9.50	7.50				
0.8WT-10P	7.2	10.30	8.30				
0.8WT-11P	8.0	11.10	9.10				



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.  
 PDWG.NO: 0013-1

**深圳市步步精科技有限公司**

NAME: 针座 0.8-4P 卧贴 米黄色

PJ. NO.: WT.17.61-73-H002


SIZE: A4 | DRW NO.:

FINISH: SEE NOTES | MAT'L.: SEE NOTES

SCALE: N/A | REV.: A0 | UNIT: mm | PAGE: 1/2

NO	物料名称	规格型号	数量(PCS)	材质	镀涂
①	基座	0.8	1	LCPE130i	本色
②	焊片	0.8	2	磷铜	锡
③	插针	0.8	2~20	磷铜	锡

REV.	ECN NO	CONTENT	DATE	ENGINEER
A0				



备注：  
 1. 包装数量：4000 /PCS/卷，10卷/箱或15卷/箱。  
 2. 包装袋长度：每卷前后各空40个空格，中间包装。  
 3. 材质：  
 载体：聚丙烯（PS），阻抗 $10^{6-9} \Omega$   
 上带：聚乙烯（PET），阻抗 $10^{6-11} \Omega$   
 卷盘：聚苯乙烯。  
 纸箱规格：345\*345\*23MM  
 纸箱规格：345\*345\*35MM

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司 .X: ±0.38    .X': ±3' .XX: ±0.25    .X': ±2' .XXX: ±0.13    .XX': ±1'		NAME: 针座 0.8-4P 卧贴 米黄色	
APPD.	JM_Zheng	PJ. NO.: WT.17.61-73-H002 SIZE: A4   DRW NO.:		FINISH: SEE NOTES    MAT'L.: SEE NOTES	
CHKD.	LYX	SCALE: N/A		REV.: A0	UNIT: mm
PDWG.NO:	0013-1	DR.	SGF	PAGE: 2/2	