





REV.	ECN NO	CONTENT	DATE	ENGINEER
A0		Initial Release	/	LHC

- 1、工作电压 Working Voltage: 30V DC;
- 2、工作电流 Working Current: 0.05A;
- 3、接触电阻 Contact Resistance:  $\leq 100m\Omega$ ;
- 4、绝缘电阻 Insulation Resistance:  $\geq 100M\Omega$ ;
- 5、动作力 Press Force:  $30\pm 15gf$ ;
- 6、寿命 Life:  $\geq 1000000$ 次。



Since 1987

步步精科技



7	铁条	SUS	-----	-----
6	盖板	PA66	黑色	-----
5	按柄	POM	红色	-----
4	簧片	磷铜	-----	-----
3	触点	纯银	-----	-----
2	基座	PA66	透明	-----
1	端子	H62Y	-----	表面镀银
NO.	DESCRIPTION	MATERIAL	COLOR	REMARK



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.

PDWG.NO: 0104-1

**深圳市步步精科技有限公司**

NAME: 小微动 带直柄 三脚插 左弯 透明基座

APPD. JM\_Zheng

CHKD. LYX

DR. LHC

PJ. NO.: WK.01.02-11-0005



SIZE: A4 DRW NO.:

FINISH: SEE NOTES MAT'L.: SEE NOTES

SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2

REV.	ECN NO	CONTENT	DATE	ENGINEER
A0		Initial Release	/	LHC

PE袋规格: 260\*185



1. 包装要求:

- 1.1 每个PE袋包装 1000 pcs ;
- 1.2 每1袋放一小纸盒;
- 1.3 每20个小纸盒放一个纸箱, 共计 20000 pcs ;
- 1.4 纸箱外贴上标签



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		 <b>深圳市步步精科技有限公司</b>	
PDWG.NO: 0104-1		APPD. JM_Zheng CHKD. LYX DR. LHC	NAME: 小微动 带直柄 三脚插 左弯 透明基座 PJ. NO.: WK.01.02-11-0005 SIZE: A4   DRW NO.: FINISH: SEE NOTES   MAT'L.: SEE NOTES SCALE: N/A   REV.: A0   UNIT: mm   PAGE: 2/2