

带灯轻触主要技术指标: Llluminated Tact Switch Main Specifications:

气候等级 Climate Grade	额定值 Rated Values	接触电阻 Contact Resistance	耐电压 Dielectric Strength	绝缘电阻 Insulation Resistance	动作力 Operating Force	寿命 Life	盐雾试验 Salt mist. Test
-25℃ 至 +75℃	30V DC, 30mA	≤0.05Ω	250V AC	≥100MΩ	260gf±50gf	10W times	12±1 hours.
-25℃ 至 +75℃	30V DC, 30mA	≤0.05Ω	250V AC	≥100MΩ	160gf±50gf	10W times	12±1 hours.

灯光选型表

灯光	灯光代码	电原理图
白光	W white	
红光	R Red	
绿光	G Green	
黄光	Y Yellow	
蓝光	BL Blue	
..		..








6	LED 灯		1	透明	白光
5	按钮	PPA	1	瓷白	借A0630
4	弹片	不锈钢	1	Ag	借A0630
3	塑座	PPA	1	黑色	借A0630
2	定位板	PPA	1	黑色	A0670
1	卡件	H62	1	Ag	借A0630
序号	名称	材料	数量	镀层/颜色	备注


THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.
PDWG,NO: 0436-1

深圳市步步精科技有限公司


.X: ±0.38 .XX: ±0.25 .XXX: ±0.13	X*: ±3* .X*: ±2* .XX*: ±1*	NAME: 轻触开关 7.6x8.7x12 侧插 白色单色灯 不锈钢弹片 260gf 瓷白按钮
APPD. JM_Zheng	CHKD. LYX	PJ. NO.: TS.43.27-21-3Z-01
DR. TSP		SIZE: A4 DRW NO.:
		FINISH: SEE NOTES MAT'L.: SEE NOTES
		SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2




元件面孔位图




电原理图



PE袋规格: 260*185



成品标签



1. 包装要求:

- 1.1 每个PE袋包装200pcs;
- 1.2 每1袋放一小纸盒;
- 1.3 每20个小纸盒放一个纸箱, 共计4000pcs;
- 1.4 纸箱外贴上标签



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
PDWG.NO: 0436-1	DR.	TSP	NAME: 轻触开关 7.6x8.7x12 侧插 白色单色灯 不锈钢弹片 260gf 瓷白按钮 PJ. NO.: TS.43.27-21-3Z-01 SIZE: A4 DRW NO.: FINISH: SEE NOTES MAT'L.: SEE NOTES SCALE: N/A REV.: A0 UNIT: mm PAGE: 2/2
	APPD.	JM_Zheng	
	CHKD.	LYX	