










RECOMMENDED P.C.B HOLE LAYOUT
COMPONENT SIDE VIEW(TOLERANCE: ± 0.05)



NOTES:

1. MATERIAL:
HOUSING: LCP, BK, UL 94V-0
SHELL: SPCC/BRASS C2680
TERMINAL: BRASS C2680
2. CONTACT PLATING:
50u" Min NICKEL UNDERPLATING OVER ALL
GOLD FLASH PLATING AT CONTACT AREA
80u" Min TIN AT SOLDERING AREA
SHELL PLATING: NICKEL 50u" Min
3. ELECTRICAL:
INSULATION RESISTANCE: 100MΩ MIN
CONTACT RESISTANCE: 30mΩ MAX
DIELECTRIC WITHSTAND: 500 VAC FOR 1Min
CURRENT RATING: 0.5A
VOLTAGE RATING: 40V
4. MECHANICAL:
INSERTION FORCE: 4.5 KGF MAX
WITHDRAWAL FORCE: 1.0~4.0 KGF
5. DURABILITY: 10000 CYCLES
6. TEMPERATURE RANGE: -55°C to +105°C



THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co., Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.

PDWG.NO: 0100-2

深圳市步步精科技有限公司

.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13 X': $\pm 3'$ X'': $\pm 2'$ X'': $\pm 1'$

NAME: HDMI 19P 2.1版 A型 母座 L=11.60 板上四脚插 平口 铁壳镀镍 无凸点 端子SMT 端子镀金G-F


APPD. JM_Zheng
CHKD. LYX
DR. TSP

PJ. NO.: 124-221-190007-V2G
SIZE: A4 DRW NO.:
FINISH: SEE NOTES MAT'L.: SEE NOTES
SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/3


REV.	ECN NO	CONTENT	DATE	ENGINEER
A0				

外壳脚规格:

规格	DIM A	DIM B	外壳脚凸点
1	2.16	1.66	无凸点
2	2.16	1.66	有凸点
3	1.50	1.50	无凸点
4	2.20	2.20	无凸点
5	1.50	1.50	有凸点





脚有凸点




脚无凸点




THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X*: ±3* .X*: ±2* .XX*: ±1*	
APPD. JM_Zheng		NAME: HDMI 19P 2.1版 A型 母座 L=11.60 板上四脚插 平口 铁壳镀镍 无凸点 端子SMT 端子镀金G-F	
CHKD. LYX		PJ. NO.: 124-221-190007-V2G	
DR. TSP		SIZE: A4 DRW NO.:	
PDWG,NO: 0100-2		FINISH: SEE NOTES MAT'L.: SEE NOTES	
		SCALE: N/A REV.: A0 UNIT: mm PAGE: 2/3	



NO. 1




NO. 2



纸箱规格: 33*33*30.5cm

NO. 4



NO. 3



1. 包装要求:

- 1.1 每卷包装500pcs, 卷带前后各空出5pcs位置;
- 1.2 每10盘放一箱, 共计5kset;
- 1.3 纸箱外贴上标签

备注:

1. 若有未装满之零数, 必须用泡棉塞满。
2. 针对于包装方式可根据客户要求包装。

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司		NAME: HDMI 19P 2.1版 A型 母座 L=11.60 板上四脚插 平口 铁壳镀镍 无凸点 端子SMT 端子镀金G-F	
.X: ±0.38	.XX: ±0.25	.X*: ±3"	.X*: ±2"	APPD.	JM_Zheng
.XXX: ±0.13	.XX*: ±1"	CHKD.	LYX	DR.	TSP
PDWG,NO: 0100-2		P.J. NO.: 124-221-190007-V2G		SIZE: A4 DRW NO.:	
		FINISH: SEE NOTES		MAT'L.: SEE NOTES	
		SCALE: N/A		REV.: A0	
		UNIT: mm		PAGE: 3/3	