



NOTE:

- MATERIAL SPECIFICATION:
  - HOUSING: HIGH TEMPERATURE RESISTANT PLASTIC, UL94 V-0.
  - CONTACTS: COPPER ALLOY
  - MID PLATE: STAINLESS STEEL
  - FRONT SHELL: STAINLESS STEEL
- PLATING SPECIFICATION:
  - CONTACTS: Ni 50 $\mu$ " MIN. UNDER PLATED OVER ALL.  
Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.  
(GOLD PLATING THICKNESS FOLLOW THE P/N)  
PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N
  - FRONT SHELL: Ni 30 $\mu$ " MIN. UNDER PLATED OVER ALL.
  - SHIELD PLATE: Ni 30 $\mu$ " MIN. UNDER PLATED OVER ALL.  
Sn 80 $\mu$ " MIN. PLATED OVER ALL
  - SHIELD PLATE&EMI PLATE: CLEAR ONLY
- MECHANICAL PERFORMANCE,
  - INSERTION FORCE: 5~20N.
  - REMOVAL FORCE: 8~20N.
  - DURABILITY: 10000 CYCLES.
- ELECTRICAL PERFORMANCE,
  - CURRENT RATING: 5.0A  
VOLTAGE RATING: 5.0V
  - LLCR:  
VBUS & GND PINS AND OTHER PINS: 40m $\Omega$  /PIN MAX.  
SHIELD: 50m $\Omega$  /MAX.  
LLCR MAX. CHANGE OF ALL PINS: 10m $\Omega$ .
  - INSULATION RESISTANCE: 100M $\Omega$  MIN
  - DIELECTRIC WITHSTAND VOLTAGE, AC 100V FOR 1 MINUTE.
- ENVIRONMENTAL PERFORMANCE:  
OPERATING TEMPERATURE: -25°C ~ +85°C.
- IR REFLOW:  
THE PEAK TEMPERATURE ON THE BOARD SHALL  
BE MAINTAINED FOR 10 SECONDS AT 260° C.



THIS DOCUMENT IS THE  
SOLE PROPERTY OF  
BBJconn Technology Co.,Ltd.  
Corporation AND SHOULD  
NOT BE USED IN WHOLE  
PRIOR WRITTEN PERMISSION.  
PDWG NO: 0366-2

.X: ±0.38	X": ±3"	NAME: TYPE-C 24P 母座 板上四脚贴 L=7.90
.XX: ±0.25	XX": ±2"	CH=1.68 双排SMT 带柱 六孔
.XXX: ±0.13	XX": ±1"	APPD JM_Zheng PJ NO: 126-221-240002-N5G
APPD JM_Zheng	CHKD LYX	SIZE:A4 DRW NO:
CHKD LYX		FINISH:SEE NOTES MAT'L:SEE NOTES
PDWG NO: 0366-2	DR WYY	SCALE:N/A REV: A0 UNIT:mm PAGE: 1/1



#### USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME
A1	GND
A2	SSTXp1
A3	SSTXn1
A4	VBUS
A5	CC1
A6	Dp1
A7	Dn1
A8	SBU1
A9	VBUS
A10	SSRXn2
A11	SSRXp2
A12	GND

PIN NUMBER	SIGNAL NAME
B12	GND
B11	SSRXp1
B10	SSRXn1
B9	VBUS
B8	SBU2
B7	Dn2
B6	Dp2
B5	CC2
B4	VBUS
B3	SSTXn2
B2	SSTXp2
B1	GND

THIS DOCUMENT IS THE  
SOLE PROPERTY OF  
BBJconn Technology Co.,Ltd.  
Corporation AND SHOULD  
NOT BE USED IN WHOLE  
PRIOR WRITTEN PERMISSION.

PDWG NO: 0366-2

APPD JM\_Zheng

CHKD LYX

DR WYY



深圳市步步精科技有限公司

X:  $\pm 0.38$  X':  $\pm 3^\circ$   
.XX:  $\pm 0.25$  X':  $\pm 2^\circ$   
.XXX:  $\pm 0.13$  X":  $\pm 1^\circ$





NAME: TYPE-C 24P 母座 板上四脚贴 L=7.90  
CH=1.68 双排SMT 带柱 六孔

PJ NO: 126-221-240002-N5G

SIZE:A4 DRW NO:

FINISH:SEE NOTES MAT'L:SEE NOTES

SCALE:N/A REV: A0 UNIT:mm PAGE: 1/1



纸箱规格: W345\*L345\*H230MM



备注:

- 1、包装数量 : 1000/PCS/卷 , 10卷/箱。
- 2、包装袋长度: 每卷前后各空10-20个空格, 中间包装。
- 3、材质:  
载体: 聚丙烯 (PS), 阻抗 $10^{6-9} \Omega$   
上带: 聚乙烯 (PET), 阻抗 $10^{6-11} \Omega$   
卷盘: 聚苯乙烯。

THIS DOCUMENT IS THE  
SOLE PROPERTY OF  
BBJconn Technology Co.,Ltd.  
Corporation AND SHOULD  
NOT BE USED IN WHOLE  
PRIOR WRITTEN PERMISSION.  
PDWG NO: 0366-2



深圳市步步精科技有限公司

.X: ±0.38	X: ±3'	NAME: TYPE-C 24P 母座 板上四脚贴 L=7.90
.XX: ±0.25	.X: ±2'	CH=1.68 双排SMT 带柱 六孔
.XXX: ±0.13	.XX: ±1'	
APPD	JM_Zheng	PJ NO: 126-221-24002-N5G
CHKD	LYX	SIZE:A4 DRW NO:
		FINISH:SEE NOTES MAT'L:SEE NOTES
		SCALE:N/A REV: A0 UNIT:mm PAGE: 2/2