

特性:

一、电气性能: ELECTRICAL

1. 额定电流: 5.0A
2. 接触阻抗: 40 MILLIOHMS MAX
3. 耐电压: 150V AC / 1 mA MAX
4. 绝缘阻抗: 150V DC/100 MEGA OHMS MIN

二、机械性能:


1. 插入力: 5~20N
2. 拨出力: 8~20N
3. 使用寿命: 10000次、拨出力 6N MIN

三、材料: MATERIAL





1. 塑胶: LCP/PA9T UL94V-0
2. 端子: C2680/C7025/C18400 T=0.20MM
3. 外壳: SUS304 T=0.30MM
4. 卡勾: SUS304 T=0.30MM

四、电镀: FINISH


1. 端子: 接触点镀金3U~MIN
PIN脚焊接区域镀金1U~MIN.
2. 外壳: 镀镍50U~MIN (盐雾48H)
- 五、电镀品需做粘锡测试: 粘锡面积达到95%以上。
- 六、SMT回流焊 (峰值260° C±5° C) 不能起泡、熔胶、变色不良 (变形在公差范围以内)
- 七、工作温度: -40° C~+85° C



剖视图




剖视图



RECOMMENDED P.C.B LAYOUT (T:1.00mm)
TOLERANCE UNSPECIFIED ±0.05mm




A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B7	D-
A6	D+	B6	D+
A7	D-	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME




THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.
PDWG. NO: 0366-2


深圳市步步精科技有限公司
NAME: TYPE-C 14P 母座 侧插 L=14.75 CH=7.20
四脚插 垫高2.76 端子DIP 端子针长1.50
P.J. NO.: UC.01.44-4W-0002
SIZE: A4 DRW NO.:
FINISH: SEE NOTES MAT'L.: SEE NOTES
SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2




① PE真空盒(1Set).




② 100PCS/盒




③ 50盒/箱(5k).



⑥ 依图示粘贴产品或ROHS标签.



⑤ 外箱用透明胶纸带封"工"字型.



④ 每箱平放25盒*2, 若尾数箱在空间处加装填充物.

备注:

1. PE真空盒1set
2. 每盒装成品100Pcs, 四周并用订书机装订;
3. 每箱装50盒(5K)
4. 外箱尺寸与规格: 45.0*25.0*35.0CM
5. 外箱用透明胶纸带封"工"字型;



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.				深圳市步步精科技有限公司			
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X': ±3' .X': ±2' .XX': ±1'		NAME: TYPE-C 14P 母座 侧插 L=14.75 CH=7.20 四脚插 垫高2.76 端子DIP 端子针长1.50			
APPD.		JM_Zheng		P.J. NO.: UC.01.44-4W-0002			
CHKD.		LYX		SIZE: A4 DRW NO.:			
DR.		LHC		FINISH: SEE NOTES MAT'L.: SEE NOTES			
PDWG. NO: 0366-2				SCALE: N/A REV.: A0 UNIT: mm PAGE: 2/2			