



REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0		Initial release	/	GZY

Note:

1. Material:
- 1.1 Housing: LCP
 - 1.2 Contact: C7025, T=0.15mm
 - 1.3 Shell: SUS304 T=0.3mm
2. ELECTRICAL:
- 2-1: CURRENT RATING: VBUS AND GND CONTACTS RATED AT 1.25A PARALLEL FOR A TOTAL OF 5A;
 - 2-2: INITIAL CONTACT RESISTANCE :40 MEGOHMS
 - 2-3: DIELECTRIC WITHSTANDING VOLTAGE: 100V AC MIN;
3. MECHANICAL CHARACTERISTICS:
- 3-1: MATING FORCE: 5~20N
 - 3-2: UNMATING FORCE: 8~20N (INITIAL), 6~20N (AFTER 10000 CYCLES)
 - 3-3: FREQUENCY: 200±50 CYCLES /HOUR, 10000 CYCLES
 - 3-4: OPERATING TEMPERATURE : -40° ~80° .



A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.

PDWG,NO: 0366-2



深圳市步步精科技有限公司

.X: ± 0.38	X*: $\pm 3^*$
.XX: ± 0.25	.X*: $\pm 2^*$
.XXX: ± 0.13	.XX*: $\pm 1^*$

APPD. JM_Zheng

CHKD. LYX

DR.	GZY
-----	-----

NAME: TYPE-C 16P 母座 直立式 外壳四脚DIP 端子SMT
H=7.40 端子C7025 不锈钢外壳 LCP黄胶 加盖编带


	PJ. NO.:
---	----------

SIZE: A4 DRW NO.:


FINISH: SEE NOTES	MAT'L.: SEE NOTES
-------------------	-------------------

SCALE: N/A	REV.: A0	UNIT: mm	PAGE: 1 / 2
------------	----------	----------	-------------


REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0		Initial release	/	GZY




① 产品入载带示意图




② 卷盘贴标签示意图



③ 7盘产品叠层示意图



⑤ 外箱封箱示意图



④ 产品入外箱示意图



	REEL	CARTON
CONNECTOR (PCS)	600	4200

包装说明:

1. 将检验好的成品;对插口朝前放入载带;每卷装600PCS产品;具体如图一所示
2. 将包装好的产品;每盘必需贴上内标签;具体如图二所示
3. 将贴好内标签的产品每7盘叠;具体如图三所示
5. 装好后并封好纸箱及贴好相关标签;具体如图五所示;
(产品包装的标签,如客户有要求,请按客户要求包装出货)
6. 载带前面留16PCS空格,后面留16PCS空格
7. COVER与CARRY剥离力:50-125g,速度:300mm/分钟左右,剥离角度:165°-180°



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION. PDWG,NO: 0366-2		深圳市步步精科技有限公司		NAME: TYPE-C 16P 母座 直立式 外壳四脚DIP 端子SMT H=7.40 端子C7025 不锈钢外壳 LCP黄胶 加盖绑带	
.X: ±0.38	X*: ±3*	PJ. NO.:		SIZE: A4 DRW NO.:	
.XX: ±0.25	.X*: ±2*	FINISH: SEE NOTES		MAT'L.: SEE NOTES	
.XXX: ±0.13	.XX*: ±1*	SCALE: N/A		REV.: A0	
APPD. JM_Zheng	CHKD. LYX	UNIT: mm		PAGE: 2/2	
DR. GZY					